

## M5 DECT Repeater



# M5

## DECT Repeater



### Key Features

- Support single- and multi-cell
- Increase the range w/o Ethernet
- Wideband audio
- Up to 5 simultaneous calls
- Daisy chaining

### Extending coverage

The snom M5 DECT Repeater is ideal for extending the range of your DECT single or multicell DECT solution in locations requiring mobile coverage across several floors or throughout large buildings.

### Handover

The repeater increases the reception range of individual bases and handsets and bridges gaps between base stations, increasing the free movement between base stations in single seamless network and allowing calls to continue uninterrupted.

### Flexibility

The M5 repeater offers superior audio quality in both wideband and narrowband calls.

### General Information

- Weight of repeater: approx. 126g
- Weight of power adapter: approx. 120g
- Dimensions: approx. (mm) 118x129x33 (WxHxD)
- Antenna diversity (two internal omni-directional antennas for better transmission and reception)
- Power: Power adapter 5,5 V 600 mA included  
Plugs: patented interchangeable clips, EU and US clip included, UK clip available optionally
- Color: black

### User Interface

- LED indicator, two colors
- Reset key

### Features

- 12 slots
- 2 simultaneous wideband calls
- 5 simultaneous narrowband calls
- Slot multiplexing
- Slot packing
- Full slot move over request

### Range

- Indoors: Up to 50 meters
- Outdoors: Up to 300 meters  
(for indoor use only)

### DECT

- Frequency bands:
  - 1880-1900 MHz (EU)
  - 1910-1930 MHz (Latin America)
  - 1920-1930 MHz (US)
- Four power levels: 14, 17, 20, 24 dBm
- Receiver sensitivity: -92 dBm
- Seamless handover
- Wideband voice (HDSP) Basic
- Interoperability, Phase I (CAT-iq 1.0, 2.0)
- DECT encryption

### Standards Conformance

- EN 301406 (TBR6)
- EN 30176 - 2 (TBR10)
- EN 60950 - 1 (Safety)
  - IEC60950 -1
  - CSA c-CSA-us / UL60950 - 1
- EN 301489 (EMC, ESD)
- RF (EMF, SAR)
- FCC part 15D, conducted & radiated
- FCC part 15B
- RSS213

### Installation

- Registration on DECT base
- Wall mounting

### Suitable for

- M700 DECT Single Cell/Multicell Base, snom PN 00003928 (EU), 00003929 (US)
- M325 DECT Single Cell bundle, snom PN 00003955 (EU), 00003954 (US)
- Handset snom M65, snom PN 00003969
- Handset snom M25, snom PN 000003987 (EU), 00003988 (US)

